

PV™ 100 Tape

Self-adhesive, cold-applied, double-sided waterproofing tape for pre-applied membrane detailing and repair

Product Description

PV™ 100 Tape is a specially formulated, two-sided, reinforced, pressure-sensitive tape. The under-side of the tape has a highly-aggressive, pressure-sensitive adhesive which is designed to adhere to penetrations, protrusions and GCP waterproofing membranes. It is cold-applied with Contact Adhesive Primer for detailing and repair of PREPRUFE® 100S pre-applied waterproofing membrane.

Applications

For use as detailing and repair aids for PREPRUFE® 100 S pre-applied waterproofing membrane and other GCP waterproofing membranes.

- End lap, T-joint lap
- Inside and outside corner
- Repair
- Other applications

Product Advantages

- Excellent bond with membrane — Excellent bond between the tape and membrane.
- Integrated waterproofing system — Fully integrated with cast concrete. The risk of water migration or leakage can be significantly reduced.
- Easy Installation — Easy to apply. Quick and simple installation.

Technical Services

For assistance with working drawings for projects and additional technical advice, please contact GCP Applied Technologies local representative.

Quality Assurance

GCP Applied Technologies (China) Company Limited Ezhou Branch is the manufacturer of PV 100 Tape. GCP Applied Technologies (China) Company Limited Ezhou Branch is certified to ISO 9001 Quality Systems, ISO 14001 Environment Management Systems, and OHSAS 18001 Occupational Health and Safety Management Systems.

Supply

Thickness (Nominal)*	0.4mm
Roll size	80mm x 20m
Rolls per carton	16 rolls
Storage	Keep ventilated and dry. Avoid long-term storage above 40 °C. Avoid exposure to rain.

Installation

Remove loose particulates from the surface of the PREPRUFE® 100 S pre-applied waterproofing membrane lower part of lap by brush and scraper, use a hot air gun to remove particulates and adhesive from the overlap area of 80mm when using PV 100 Tape. unroll the tape on the exposed HDPE surface (after removal of particulate) of the membrane and adhere to the membrane. Use heavy, hand pressure or a hand roller to maximise adhesion. Remove the release liner during application.

For advice on other applications, e.g. corner, pile, penetration or repair, please refer to GCP Technical Services.

PV 100 Tape is not designed to be exposed to direct sunlight. A piece of PV 100 membrane exceeding the tape area is to be installed to offer adequate protection against UV light. Contact GCP Technical Services for clarification when in doubt.

Health and Safety

Please refer to relevant Material Safety Data Sheet (MSDS).

gcpat.ae | United Arab Emirates customer service: +971 4 5139560

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

PV is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2021 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140, USA

Emirates Chemicals LLC., P. O. Box 5006, Office 2104, 21 Floor, The Exchange Tower, Opp. JW Marriott Marquis Hotel, Business Bay, Dubai – United Arab Emirates

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

P. O. Box 5006, Office 2104, 21 Floor, The Exchange Tower, Opp. JW Marriott Marquis Hotel, Business Bay, Dubai – United Arab Emirates

This document is only current as of the last updated date stated below and is valid only for use in the UAE. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.ae. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-15

gcpat.ae/solutions/products/preprufe-pre-applied-waterproofing-solutions/pv-100-tape