

LASOL 91 M

Release agent

Product Description

LASOL 91 M is a release agent for steel molds that creates a smooth surface free of stains.

Application

The product is best applied with a pressure sprayer (3–6 bar). Apply in a thin and even coat on the clean and dry surface. LASOL 91 M can also be applied with a brush or sponge, provided that a thin, continuous film is achieved.

Special Features

LASOL 91 M contains corrosion inhibitors to prevent rust formation on steel forms.

LASOL 91 M is also ideally suited for heated molds, up to 70 °C.

Recommended Application Rate

Packaging

1.000 L Container; 210 L Drum; 35 L Canister

Typical Properties

Color	Light Yellow
Physical form	Liquid
Density (kg/dm ³)	0,89

Storage

Store in original container away from extremes of cold or heat

Shelf Life

Approximately 1 year in original unopened container.

Safety

Skin and eye irritation are possible with contact. Please consult SDS (Safety Data Sheet).

gcpat.ae | United Arab Emirates customer service: +971 4 5139560

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right

LASOL is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status

© Copyright 2018 GCP Applied Technologies Inc. All rights reserved.

Pyrmonter Straße 56, 32676 Lügde

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

P. O. Box 5006, Office 2104, 21 Floor, The Exchange Tower, Opp. JW Marriott Marquis Hotel, Business Bay, Dubai – United Arab Emirates

This document is only current as of the last updated date stated below and is valid only for use in the UAE. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.ae. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-15

gcpat.ae/solutions/products/lasol-91-m